



**ACRY-TECH COATINGS INC.**

3601 NE 5th Avenue • Ft. Lauderdale, FL 33334

email: sales@acrytech.com • www.acrytech.com

Design & Manufacture of Architectural & Specialty Coatings

Phone 954-565-6001  
Fax: 954-565-2864  
Toll Free 800-771-6001

# SolarX Enamel

**SolarX Enamel** is a highly reflective bright white waterbased acrylic coating that gives great performance and a beautiful, easy to maintain gloss sheen over primed or bare metal substrates. **SolarX Enamel** reflects over 80% of the sun's rays and reduces surface and substrate temperatures. **SolarX** is easy to maintain and clean so the heat reflective qualities can be maintained for years longer than with soft elastomeric type coatings. It is VOC compliant and is an excellent maintenance coating for most industrial metal substrates or decorative applications. Durable, beautiful and tough, **SolarX Enamel** also protects against corrosion while beautifying. Use **SolarX** for roofs on busses, trailers, campers, shipping containers, metal buildings or any other metal substrate where heat reduction is required.

**Surface Preparation:** Surfaces must be solid, clean and free of all oil, grease, loose paint, silicones, scaling rust and biological growth. Prepare surface by sandblasting or pressure washing. Prime bare or rusting metal with **Acry-Tech Metal Primer WB** for additional durability and longevity. *See our maintenance guide for preparation & application procedures.*

**Application:** This product can be applied by airless sprayer, HVLP, brush or roller. Apply generously using overlapping strokes. Textured and porous surfaces will require more coating. Do not apply this coating to a wet surface or when surface temperature is or will be below 50 degrees F. Apply only to sound substrates. Wash spills and tools immediately with soapy water. *See our maintenance guide for application procedures.*

**Technical Data:**

Wt per gallon (#) 9.0 - 9.6	UV Resistance - Excellent
Viscosity 5 - 8 Kcps	VOC-190g/L or 1.6# / gal.
Max Spread Rate: 200 - 225 sf/gal @ 2 - 2.25 dry mils	Solids Volume: 22% - 27%

**HMIS Ratings:**

HEALTH 1    FLAMMABILITY 0    REACTIVITY 0  
PERSONAL PROTECTION: HANDLING B    APPLICATION G

**Cautions:** KEEP FROM FREEZING. USE ONLY WITH ADEQUATE VENTILATION. WEAR NIOSH APPROVED ORGANIC VAPOR CARTRIDGE MASK WHEN APPLYING OR SANDING IN CONFINED AREA. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE, KEEP OUT OF THE REACH OF CHILDREN! AVOID EYE & SKIN CONTACT. WEAR GOGGLES. **DOES NOT CONTAIN LEAD!**