



ACRY-TECH COATINGS INC.

3601 NE 5th Avenue • Ft. Lauderdale, FL 33334

email: sales@acrytech.com • www.acrytech.com

Design & Manufacture of Architectural & Specialty Coatings

Phone 954-565-6001
Fax: 954-565-2864
Toll Free 800-771-6001

SUPER ROOF SEAL

EXCEPTIONAL WATER RESISTANCE & DURABILITY
UNIQUE **SELF CROSS-LINKING** GIVES INCREDIBLE TOUGHNESS

It's our incredible "**SELF-CROSSLINKING**", Bright White, Water-Tight, Rubbery Coating that prevents roof leaks and stays flexible and watertight for years. It contains extra **Bioquell™** to fight off the damaging effects of mold, mildew, fungus and algae. **Super Roof Seal** stops leaks, often eliminating the need for expensive repairs or reroofing. Unlike some so-called elastomerics, **Super Roof Seal** stays flexible even under low wintertime temperatures. Acry-Tech Elastomerics have been proven for over 24 years and successfully stood up to **Hurricane Andrew, Hurricane Floyd and Hurricane Irene** by giving great wind and water resistance to thousands of homes in South Florida and the Bahamas! Use it on Cement Tile, Barrel Tile, Shingle or Metal Roofs for long lasting protection at a low, low cost and dramatically higher durability and performance than "Home Store" brands. Acry-Tech's aggressive research has designed this product with a unique and **Revolutionary "Self Cross-Linking" Technology** that makes **Super Roof Seal** vastly TOUGHER & MORE WATERPROOF than the competition!

ADVANTAGES:

Fully Self Cross-Linked for the Ultimate in Toughness and Water Resistance - Tremendous Value
Contains **Bioquell™** to fight fungus and mildew - Flexible At Low Temps - Incredible Durability
Stops Wind Blown Water Penetration - Completely Encapsulates Roof Components
Heat Reflective, lowers A/C costs - No Blistering! - Easy To Apply - High Build

SURFACE PREPARATION: Pressure clean to remove all loose coatings, chalk, biological growth, oil, rust or other contaminants. Prime chalking surfaces with **Acry-Tech Primer**. Prime rusting metal with **Metal Primer WB**. Apply **Therm-X** elastomeric basecoat to fill cracks and gaps between tiles, on shingles & for the seams and fasteners on metal roofs. **Therm-X**, a flexible, lightweight and easy to use basecoat will seal the surface to provide an even monolithic substrate for application of **Super Roof Seal**. **Therm-X** with over 700% elongation is the ultimate basecoat for **Super Roof Seal**.

APPLICATION: Use airless sprayer, brush or roller and apply generously. Textured and porous surfaces will require more coating. A two coat application rate of 80 sf per gallon per coat yields 20 dry mils for great water tight protection for cement tile roofs, shingle and mineral surfaced roofing. A three coat application is recommended for low slope roofing. **Metal Roofs** are well protected with a heavy coat of **Super Roof Seal** after fasteners and seams have been sealed with **Therm-X**. Use **Super Roof Seal** as the topcoat over our other roof elastomerics or use it as the base and topcoat for simplicity. Do not apply this coating to a wet surface, or when rain or dew is imminent. Do not apply when surface temperature will be below 50°F. Wash spills and tools immediately with soapy water.

TECHNICAL DATA: Solids Vol. 50% Color: Heat Reflecting White Wt per gal 11.8# Visc: 16-20 Kcps
Fully Self Cross-Linked (Proprietary Process) for Incredible Toughness & Excellent Water Resistance

HMIS RATINGS: HEALTH - 1 FLAMMABILITY - 0 REACTIVITY - 0 PERS. PROT.: HANDLING - B APPLICATION - G

CAUTIONS: KEEP FROM FREEZING. USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE, KEEP OUT OF THE REACH OF CHILDREN! AVOID EYE CONTACT. WEAR GOGGLES. MAY TEMPORARILY INHIBIT GRASS GROWTH UNDER ROOF DRIP EDGE DUE TO HIGH LEVEL OF BIOQUELL™ TO PREVENT BIOLOGICAL GROWTH ON THE ROOF.

WARRANTY: No blanket warranty of merchantability or fitness for a particular purpose is given either expressly or implied. ACI will warrant product on a job basis through authorized dealers with prior approvals from ACI.