



ACRY-TECH COATINGS INC.

3601 NE 5th Avenue • Ft. Lauderdale, FL 33334

email: sales@acrytech.com • www.acrytech.com

Design & Manufacture of Architectural & Specialty Coatings

Phone 954-565-6001
Fax: 954-565-2864
Toll Free 800-771-6001

COOL TOP

Cool Top is a long lasting white acrylic roof paint that dramatically cuts heat, effectively increasing the life of asphalt and modified bitumen roofs. You get great durability and beauty while the bright white (“non-browning”) finish reflects the sun’s heat, dramatically lowering the temperature of the roof compared to typical aluminum coatings. When your roof stays cooler, the essential oils within the asphalt don’t bake and dry out and that means your roof will last longer! AND, the cooler surface of the roof makes the structure cooler and more comfortable and puts less strain on your A/C system, while saving money on air conditioning costs. **Cool Top** lasts years longer than aluminized asphalt coatings and can be applied with airless spray equipment so you don’t have to carry 5-gallon pails up stairways, ladders and elevators, and without the mess of removing buckets from the roof top. The hi-tech **Cool Top** formula, designed specifically for asphaltic surfaces, bonds exceptionally well and resists browning, staying white while standing up to ponding water which is common to most flat roofs. Use **Cool Top** on Flat or Sloped Asphalt, Asphalt Shingles and Modified Bitumen Roofs whether smooth surfaced or granulated.

UV Resistance, Ponding Resistance, Heat Reduction... You get all three!

Surface Preparation: Surfaces must be clean and free of all loose or chalking paint, loose granules, and all biological growth and oxidation. Pressure wash to remove dirt, loose or chalking coatings, oxidation and biological growth. Severely chalking asphalt should be primed with **Diamond Glaze** (solvent based acrylic) for deep penetration into the weathered asphalt for maximum adhesion of the **Cool Top**. Granulated surfaces do not need primer!

Application: **Cool Top** can be applied by airless sprayer, brush or roller. A two coat application at 200 sf / gal. per coat will give the best coverage and will result in the longest lasting results. Do not apply this coating to a wet surface, when rain or evening dew is imminent, or when surface temperature is or will be below 50 degrees F. Wash spills and tools with soapy water.

Technical Data: Wt per gal.(#) 11.5 Color – Bright White UV Resistance - Excellent!
Recommended Use Rate: Smooth Asphalt-125 sf / gal. Granulated-100 sf / gal.

HMS Ratings: HEALTH 1 FLAMMABILITY 0 REACTIVITY 0 PERS. PROT.: HANDLING B APPLICATION G

Cautions: KEEP FROM FREEZING. USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF THE REACH OF CHILDREN! CONTAINS CRYSTALLINE SILICA. WEAR NIOSH APPROVED MASK IF APPLYING IN CONFINED AREA. AVOID EYE CONTACT. WEAR GOGGLES.

Warranty: No warranty of merchantability or fitness for a particular purpose is given either expressly or implied. ACI will however, replace at its MFG facility any of its products which are determined by ACI to have a manufacturing defect.

Packaging Availability: Available in 5’s or in drums as special order.