ACRY-TECH COATINGS INC.
3601 NE 5th Avenue • Ft. Lauderdale, FL 33334
email: sales@acrytech.com • www.acrytech.com
Phone 954-565-6001
Fax: 954-565-2864
Toll Free 800-771-6001
Design & Manufacture of Architectural & Specialty Coatings

AquaGuard Primer

(CONCENTRATE)

AquaGuard Primer is a concentrated, deep-penetrating, surface conditioning, adhesive and when diluted, it drives deeply into raw or coated exterior concrete, stucco or block. It's also excellent for priming **'HOT STUCCO'** after only a 5 day cure time. It's fungus resistant and aids in penetrating chalky surfaces and "holding out" finish coats on porous surfaces. ***AquaGuard Primer*** greatly increases adhesion between the substrate and coating and also significantly reduces application costs through product savings and reduced labor. Coating or paint glides on easily over the primed surface.

Eliminate Blisters or Peeling FOREVER!

Surface Preparation: All surfaces must be clean and solid and free of all oil, loose paint, biological growth or other foreign matter. New Surfaces: Remove grease, oil and efflorescence. Dull glossy surfaces. Previously Painted Surfaces: Dull glossy surfaces. Remove loose coatings, chalk, efflorescence, rust, biological growth, oil or any other surface contaminants.

Applying the Primer: This product is a concentrate, *you must dilute as follows*: To one part of this Concentrated Primer, add 3 to 4 parts of clean water by volume and stir until uniform. For surfaces that are extremely porous or chalky, use the 4:1 dilution ratio and apply the primer mixture more heavily to assist maximum penetration. If the surface is less porous or has only light chalk, use the 3:1 dilution ratio. In no event must less than 3 gallons of water be added to a gallon of Primer Concentrate as penetration will be sacrificed and application of subsequent coatings will be more difficult due to the excessively glossy surface that will result. Once diluted and thoroughly mixed, this product can be applied by brush, roller, or airless sprayer at the rate of 300 square feet per gallon of the 3:1 diluted primer mix, or 250 square feet per gallon of the 4:1 diluted primer mix. Stir well before & during use.

Technical Data: Odor - Slight Ammonia Weight per gal. 8.9# Dries Clear

HMIS Ratings: HEALTH 2 FLAMMABILITY 0 REACTIVITY 0
PERSONAL PROTECTION: HANDLING B SPRAYING G

Cautions: KEEP FROM FREEZING. USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF THE REACH OF CHILDREN! AVOID EYE CONTACT. WEAR GOGGLES.

Warranty: No warranty of merchantibility or fitness for a particular purpose is given either expressly or implied. ACI will however, replace at its manufacturing facility any of its products determined by ACI to have a manufacturing defect.