



ACRY-TECH COATINGS INC.

3601 NE 5th Avenue • Ft. Lauderdale, FL 33334

email: sales@acrytech.com • www.acrytech.com

Design & Manufacture of Architectural & Specialty Coatings

Phone 954-565-6001
Fax: 954-565-2864
Toll Free 800-771-6001

SUPREME ROOF

WITH BIOQUELL™

Supreme Roof is the ultimate, longest lasting, velvet sheen, acrylic roof finish available anywhere! This premium roof finish gives fantastic durability and beauty on Concrete Tile Roofs, Bermuda Roofs, Shingle Roofs and is a great choice as a topcoat for Elastomeric Roof Coatings or other surfaces. Our unique **Bioquell** system gives you the longest term mildew, mold, fungus and algae protection in the industry for brilliant, long lasting beauty.

AVAILABLE IN PURE BRIGHT WHITE & BEAUTIFUL COLORS, TOO!

Surface Preparation: Surfaces must be clean and free of all oil, loose or chalking paint, silicones and all biological growth. **New Surfaces:** Prime bare concrete with **Acry-Tech Primer**. Prime bare metal with **Acry-Tech Metal Primer**. **Previously Painted Surfaces:** Remove loose dirt, chalking paint and biological growth. Prime concrete and porous surfaces with **Acry-Tech Primer**. Prime rusting metal surfaces with **Acry-Tech Metal Primer**.

Application: This product can be applied by airless sprayer, brush or roller. Apply generously with overlapping strokes. Textured and porous surfaces will require more coating. Do not apply this coating to a wet surface or when surface temperature is or will be below 50 degrees F. Wash spills and tools with soapy water.

Technical Data: Wt per gal.(#) 11.1 Visc. 6-8 Kcps UV Resistance - Excellent!
Recommended Coverage Rate: 200 sq. ft. per gallon over WP
Apply at 150 sf/gal over bare concrete

HMIS Ratings: HEALTH 1 FLAMMABILITY 0 REACTIVITY 0 PERS. PROT.: HANDLING B APPLICATION G

Cautions: KEEP FROM FREEZING. USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF THE REACH OF CHILDREN! AVOID EYE CONTACT. WEAR GOGGLES.

Warranty: No warranty of merchantability or fitness for a particular purpose is given either expressly or implied. ACI will however, replace at its MFG facility any of its products which are determined by ACI to have a manufacturing defect.

Availability: Available in 1's, 5's or in drums or customer's own clean containers.