



AQUAGUARD **BONDING PRIMER** **(CONCENTRATE)**

AquaGuard Bonding Primer is a concentrated, **CLEAR**, deep-penetrating, surface conditioning, adhesive and when diluted, it drives deeply into raw concrete, stucco, block, porous wood, or other porous surfaces. It's also excellent for priming 'HOT STUCCO' after only a 5 day cure time. It locks in residual chalk after pressure washing to insure great adhesion for repainting. **AquaGuard Bonding Primer** gives great "hold-out" on porous surfaces so finish coats go on smoothly with maximum yield. **AquaGuard Bonding Primer** greatly increases adhesion between the substrate and coating and also significantly reduces application costs through product savings and reduced labor. Your paint or coating will glide on the **AquaGuard** sealed surface

Eliminate Blisters or Peeling FOREVER!

Surface Preparation: All surfaces must be clean and solid and free of all oil, loose paint, biological growth or other foreign matter. **New Surfaces:** Remove grease, oil and efflorescence. Dull glossy surfaces. **Previously Painted Surfaces:** Dull glossy surfaces. Remove loose coatings, chalk, efflorescence, rust, biological growth, oil or any other surface contaminants.

Applying the Primer: This product is a concentrate, *you must dilute as follows:* To one part of this Concentrated Primer, add 3 to 4 parts of clean water by volume and stir until uniform. For surfaces that are extremely porous or chalky, use the 4:1 dilution ratio and apply the primer mixture more heavily to assist maximum penetration. If the surface is less porous or has light chalk, use the 3:1 dilution ratio. In no event must less than 3 gallons of water be added to a gallon of **AquaGuard Bonding Primer Concentrate** as penetration will be sacrificed and application of subsequent coatings will be more difficult due to the excessively glossy surface that may result. Once diluted and thoroughly mixed, this product can be applied by brush, roller, or airless sprayer at the rate of 250 square feet per gallon of the 3:1 diluted primer mix, or 200 square feet per gallon of the 4:1 diluted primer mix. Stir well before & during use.

Technical Data: Weight per gal. 8.5# Color: Milky White when wet but dries clear.
Solids Wt.- 51% (undiluted) VOC – 0.63#/gal. 76g/L, 3.8%/wt. (undiluted)
Dilution Rate prior to Application: 3 parts water by volume to 1 part Primer Concentrate

HMIS Ratings: HEALTH 2 FLAMMABILITY 0 REACTIVITY 0
PERSONAL PROTECTION: HANDLING B SPRAYING G

Cautions: KEEP FROM FREEZING. USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF THE REACH OF CHILDREN! AVOID EYE CONTACT. WEAR GOGGLES.

Warranty: No warranty of merchantability or fitness for a particular purpose is given either expressly or implied. ACI will however, replace at its manufacturing facility any of its products determined by ACI to have a manufacturing defect.