Safety Data Sheet

Issue Date: 20-Nov-2013 Revision Date: 15-Sep-2020 Version 2

1. IDENTIFICATION

Product identifier

Product Name SOFT TREAD

Other means of identification

SDS # SOTPM/SOTU

Recommended use of the chemical and restrictions on use

Recommended Use Prevents slips or falls and generally creates a safe footing on concrete, wood, metal, and

other substrates.

Details of the supplier of the safety data sheet

Manufacturer Address Acry-Tech Coatings, Inc. 7241 Haverhill Business PKWY Suite 108

Riviera Beach, FL 33407

Emergency telephone number

Company Phone Number 1-800-771-6001

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance White or colored viscous Physical state Liquid Odor Mild characteristic

gritty liquid

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Xvlene	1330-20-7	<1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek

medical attention.

Skin Contact Wash off immediately with soap and plenty of water. If skin irritation persists, call a

physician.

Inhalation Remove to fresh air. Seek medical attention.

Ingestion Drink 1 or 2 glasses of water. Call a physician.

Most important symptoms and effects, both acute and delayed

Symptoms Breathing vapors may result in headaches, nausea, and irritation to the lungs. May cause

dermatitis or irritation in some individuals upon prolonged contact. Exposed individuals may experience eye tearing, redness and discomfort. Prolonged contact may cause irreversible

damage to eye. May cause nausea, vomiting, stomach ache, and diarrhea.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical.

Unsuitable Extinguishing Media Water aggravates spill clean up.

Specific Hazards Arising from the Chemical

Material can splatter above 100 degrees Celsius. Dried film may burn.

Hazardous combustion products Carbon oxides. Nitrogen oxides (NOx).

Explosion Data

Sensitivity to Mechanical Impact Not applicable.
Sensitivity to Static Discharge Not applicable.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions If in a confined area, NIOSH approved respiratory protection may be required. Keep

spectators away.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Recover free liquid. Spread material evenly on a plastic film and allow to dry thoroughly.

Dispose of in accordance with federal, state and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Avoid breathing product vapors. Deliberate ingestion or concentrating and inhaling of

vapors may be harmful or fatal. See label precautions. Avoid contact with eyes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect containers

from rupture. Keep from freezing. Store between 40° and 120°F (4° and 49°C).

Substances that are incompatible with water. Oxidizers. **Incompatible Materials**

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	

Appropriate engineering controls

Local exhaust ventilation recommended. **Engineering Controls**

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear approved safety goggles where a splash hazard exists.

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, **Skin and Body Protection**

as appropriate, to prevent skin contact.

Respiratory Protection For spills or overexposure wear NIOSH approved respiratory protection with organic vapor

cartridges.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance White or colored viscous gritty liquid Odor Mild characteristic Color White or colored **Odor Threshold** Not determined

Remarks • Method Property Values

8.0-9.0 pН

0 °C / 32 °F > 100 °C / >212 °F Melting point / freezing point

Boiling point / boiling range

Flash point Not established (water based product)

Evaporation Rate < 0.1 Flammability (Solid, Gas) n/a-liquid

Flammability Limit in Air

Upper flammability or explosive Not applicable

limits

Lower flammability or explosive Not applicable

limits

Vapor Pressure Not established **Vapor Density** Not established

Relative Density 1.2-1.25 @ 60°F (ASTM D 1298)

Water Solubility Not determined Solubility in other solvents Not determined

Property Values Remarks • Method

Partition Coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
Dynamic Viscosity
Explosive Properties
Not determined

Other information

VOC Content 0.00 lb/gal; 0 g/L Liquid Density 10.1 lb/gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures >100 °C.

Incompatible materials

Substances that are incompatible with water. Oxidizers.

Hazardous decomposition products

Carbon oxides. Nitrogen oxides (NOx).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact Avoid contact with skin.

Inhalation Avoid breathing vapors or mists.

Ingestion Do not taste or swallow.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350	= 29.08 mg/L (Rat) 4 h = 5000
1330-20-7		mg/kg (Rabbit)	ppm (Rat)4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested. Group 3 IARC components are "not classifiable as human carcinogens".

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene		Group 3		
1330-20-7				

Legend

IARC (International Agency for Research on Cancer)
Group 3 IARC components are "not classifiable as human carcinogens"

Numerical measures of toxicity

Not determined.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Based on ecotoxicity and environmental data for the individual ingredients in this specific formulation and for related cleaning product formulations, it is expected that this product would exhibit a non-hazardous order of toxicity at relevant environmental concentrations.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Xylene		13.1 - 16.5: 96 h Lepomis	0.6: 48 h Gammarus lacustris mg/L
1330-20-7		macrochirus mg/L LC50	LC50 3.82: 48 h water flea mg/L
		flow-through 19: 96 h Lepomis	EC50
		macrochirus mg/L LC50 23.53 -	
		29.97: 96 h Pimephales promelas	
		mg/L LC50 static 7.711 - 9.591: 96 h	
		Lepomis macrochirus mg/L LC50	
		static 780: 96 h Cyprinus carpio	
		mg/L LC50 semi-static 2.661 -	
		4.093: 96 h Oncorhynchus mykiss	
		mg/L LC50 static 30.26 - 40.75: 96 h	
		Poecilia reticulata mg/L LC50 static	
		13.5 - 17.3: 96 h Oncorhynchus	
		mykiss mg/L LC50 13.4: 96 h	
		Pimephales promelas mg/L LC50	
		flow-through 780: 96 h Cyprinus	
		carpio mg/L LC50	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Xylene	3.15
1330-20-7	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene		Included in waste stream:		U239
1330-20-7		F039		

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
Xylene	Х	ACTIVE	Х	X	X	Χ	Χ	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ

SARA 311/312 Hazard Categories

Not applicable

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb			X

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Xylene	X	X	X
1330-20-7			

16. OTHER INFORMATION

Instability

Special Hazards

NFPA Not determined **Personal Protection** HMIS **Health Hazards Flammability** Physical hazards

Not determined

Flammability

Issue Date: 20-Nov-2013 **Revision Date:** 15-Sep-2020 **Revision Note:** Address change

Health Hazards

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet